



UNITED CENTRAL
INDUSTRIAL SUPPLY®

SUBSIDIARIES



**UNITED CENTRAL & KOEHLER:
PROVEN LEADERS IN CAP LAMP TECHNOLOGY SINCE 1910**



CORDLESS CAP LAMP - LI 6000

PRODUCT FEATURES

- » MSHA Approved
- » Eye Guard protected
- » Charge time: 6 hours
- » Run time: 16 hours
- » Weight: 5 oz.
- » Manufactured in the U.S.
- » Multiple options for recharging
- » Single unit charger
- » Dedicated locking 50-unit charger reduces loss



The Right Products. At The Right Place. With The Right Support.

www.unitedcentral.net



LOCKING 50-UNIT CHARGER
(reduces loss)



SINGLE-UNIT CHARGER



ECONOMY SINGLE-UNIT CHARGER

LI-6000-G SPECIFICATIONS

Bulb/Lamp: Luxeon Rebel LED

Bulb/Lamp Life: 50000 Hours

Total Light Output: 45 Lumens

Peak Beam Intensity: 5300 Candela

Beam Distance: 140 meters

Run Time: 13 Hours "High" mode
16 Hous "Low" mode

Impact Resistance: 1 meter

Ingress Protection: "Submersible" - IP68 @ 1m for .5 hours

Power Source: Single Lithium Ion 18650 (2600 mAh capacity)

Charge Time: <6 hours

Operating Temperature: -20C° to +60C°

Regulated light output. Unit maintains optimum brightness for entire runtime.

Multiple lighting modes

1st Switch Press – Low Setting, 25% Brightness

2nd Switch Press – High Setting, 100% Brightness

3rd Switch Press – Off

Easy-to-view LED Charge Status Indication

Red – Normal Charging Operation is in Progress

Green – Fully Charged

Automatic Low Cell Power Detection and Indication

Switches to 25% Brightness Setting Upon Low Cell Charge

Blinks Once Each Minute to Remind the User of Low Charge

MSHA Approval #19-A11001-0

Unit Dimensions:

Length: 3.4" x 2.4" x 2.7"

Weight: 5.0 oz

